



# PHOTONFOIL

## Data sheet

## Product code P33

Technical Data			
Width (effective)	1200	mm	EN 822
Flap	50	mm	EN 822
Yield	12	m <sup>2</sup>	
Thickness	33	mm	EN 823
Weight	0.95	kg/m <sup>2</sup>	
Core R value (90/90)	0.97	W/m.k	EN 16012
R value (90/90) with 2 x 20mm air spaces	2.35	W/m.k	EN 16012
Emissivity (90/90)	Measured 0.02		EN 16012
	Declared 0.05		
Vapour barrier	>6,000	MN.s/g.m	EN 12572 :2001
Air barrier	Practically zero	m <sup>3</sup> /h.m <sup>2</sup> @ 100 Pa	EN 9237
Fire performance	Class E		EN 11925-2

Packaging Data			
Roll length	10	m	
Roll diameter	400	mm	
Roll weight	12	Kg	
Rolls per pallet	18		

Thermic Technology Limited  
Moorland Gate Business Park  
Chorley  
PR6 9FE

Tel: 01257 241084  
Fax: 0161 883 1340

[www.photonfoil.co.uk](http://www.photonfoil.co.uk)  
[info@thermictechnology.co.uk](mailto:info@thermictechnology.co.uk)

Issued March 2017